


TYPICAL NOTES:

- 1) REFER TO SHEET A-3.0 FOR TYPICAL ASSEMBLIES.
- 2) WINDOW AND PATIO DOORS REFERENCED ARE GENERAL SIZES. MATCH TO BE CHOSEN BY OWNER.
- 3) PROVIDE BATT INSULATION AT ALL FLOOR AND WALL CAVITIES FOR SOUND ATTENUATION.
- 4) INTERIOR DOORS TO BE INSTALLED 4 1/2" FROM ADJACENT WALL U.N.O.
- 5) VERIFY ALL WINDOW/DOOR ROUGH OPENINGS WITH WINDOW MANUFACTURER PRIOR TO ANY WORK.
- 6) SEE BUILDING ELEVATIONS FOR WINDOW/DOOR HEADER HEIGHTS.
- 7) WEAR ALL OPENINGS WITH 15 # FELT AND PROVIDE 1 1/2" HEAD FLASHING. (PAINT TO MATCH SIDING).
- 8) PROVIDE BLOCKING IN WALLS FOR ALL CABINETS AND ACCESSORIES.
- 9) PROVIDE MOISTURE RESISTENT-DRYWALL AT ALL WET WALLS. (AT SHOWER, BEHIND SINK, BEHIND TUB, ETC.)
- 10) ALL EXTERIOR WALLS TO HAVE R-21 BATT INSULATION OR BLOWN IN.

1 LOWER FLOOR PLAN

A-1.0 SCALE: 1/4" = 1'-0"

FINISHED: 1308 SF
UNFINISHED: 1348 SF



SHEET #
A-1.0

REVISIONS

DATE
8/29/14

PROJECT #
S14-005

CUSTOM HOME
9910 FALCON ROOST POINT
PARKER, COLORADO 80138

WAYNE BLOCK HOMES
17268 WATERHOUSE CIR UNIT E
PARKER, COLORADO 80134
PH (303)902-5633

SEIDL DESIGN
GROUP INC.
PO BOX 82460
PORTLAND, OR
97222
(503)970-6283
seid@seidgroup.com

